substrate (1).

(19) World Intellectual Property **Organization**

International Bureau





(43) International Publication Date 17 February 2005 (17.02.2005)

(10) International Publication Number WO 2005/015647 A1

(51) International Patent Classification7: 21/30

H01L 33/00,

(21) International Application Number:

PCT/KR2003/001600

- (22) International Filing Date: 8 August 2003 (08.08.2003)
- (25) Filing Language:

English

(26) Publication Language:

English

- (71) Applicant (for all designated States except US): VICHEL INC. [KR/KR]; 317. Jang Bldg. 92-6, Yangjae1-dong, Seocho-gu, Seoul 137-890 (KR).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): KANG, Sang-kyu [KR/KR]; 208-302 Moklyun apt., 1052, Hogae-dong, Dongan-ku, Anyang-City, Gyconggi-do 431-080 (KR).
- (74) Agents: KIM, Dong-Jin et al.; Marcopolo Bldg 31; 720-20 Yeoksam-Dong, Gangnam-gu, Seoul 135-080 (KR).


- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: NITRIDE MICRO LIGHT EMITTING DIODE WITH HIGH BRIGHTNESS AND METHOD OF MANUFACTURING



large area is formed thereon, so that all the luminous pillars can be driven at the same time. In addition, the present invention provides a nitride micro LED with high brightness in which uniformity in formation of electrodes on the micro-sized luminous pillars array is enhanced by employing a flip-chip structure.